

OMNITRONIC XPA-4804 MK2 Amplifier

Class D PA amplifier with limiter, 4 x 1800 W RMS (2 ohms), 4 x 1200 W RMS (4 ohms)

Art. No.: 10451010

GTIN: 4026397731316



List price: 772.31 €

incl. 19% VAT.

Features:

- 3 operating modes can be selected (stereo, parallel or bridged)
- Input sensitivity adjustable
- Level control per channel
- Electronically balanced inputs via XLR mounting jacks, with XLR feed-through outputs
- Speaker outputs via lockable Speaker plugs
- Highly efficient air flow from front to rear
- The device is cooled by cooling fan
- (19") 48.3 cm rack installation 2 U
- For application areas such as: Clubs/dancing school; installation; mobile use; mobile djs / entertainer; restaurants, bars and hotels; rental; sports centres/gyms

Package contents

- 1 x amplifier, 4 x foot, 1 x user manual

Logistic

EAN / GTIN: 4026397731316

Weight: 15,30 kg

Length: 0.56 m

Width: 0.43 m

Height: 0.14 m

Technical specifications:

| | |
|--------------------|--|
| Power supply: | 230 V AC, 50 Hz |
| Power consumption: | 1380 W 1/8 power |
| Protection class: | Protection class I |
| Output power: | 4 x 1800 W RMS (2 ohms) 4 x 1200 W RMS (4 ohms) 4 x 800 W RMS (8 ohms) 2 x 2500 W RMS bridged (4 ohms) 2 x 2400 W RMS bridged (8 ohms) |

| | |
|--------------------|--|
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Frequency range: | 20 - 20000 Hz |
| S/N ratio: | >102 dB |
| THD: | <0,1 % at 1 kHz |
| Cooling: | 2 x cooling fan , air flow from front to rear |
| Impedance: | Input: 20 kOhm , bal. Input: 10 kOhm , unbal. |
| Gain: | 40 dB/ 0,775 V 38 dB/ 1 V 32 dB/ 2 V |
| Housing color: | Black |
| Circuitry: | Class D |
| Slew rate: | >30 V/ μ s |
| Damping factor: | >500 |
| Control elements: | Power switch, level control per channel, mode switch (stereo/parallel/bridged), Input sensitivity switch |
| Controls: | Overheat; overload; short-circuit; softstart; DC voltage; VHF; current limiting; limiter |
| Status LED: | Power, signal, clip, protect |
| Connections: | Input: line via 4 x 3-pin XLR (F) mounting version Link: line via 4 x 3-pin XLR (M) mounting version Output: speaker via 4 x speaker built-in socket (F) |
| Input sensitivity: | 0,775 V; 1 V; 2 V , switchable |
| Housing design: | (19") 48.3 cm rack installation 2 U |
| Dimensions: | Width: 48,3 cm Depth: 33,0 cm Height: 8,8 cm |
| Weight: | 14,20 kg |