

## CELTO ACOUSTIQUE C2.20 Amplifier

Class TD core amplifier, 2 x 2000 W RMS (4 ohms), 2 x 1200 W RMS (8 ohms)

Art. No.: 11043809

GTIN: 4026397745597



**List price: on demand €**

incl. 19% VAT.

### Features:

- (19") 48.3 cm rack installation 2 U
- Highly efficient air flow from front to rear
- The device is cooled by temperature-controlled fan

#### Package contents

- 1 x amplifier, 1 x power cord, 4 x foot

### Logistic

EAN / GTIN: 4026397745597

### Technical specifications:

|                   |   |
|-------------------|---|
| Power supply:     | 230 V AC, 50 Hz   |
| Protection class: | Protection class I  |
| Output power:     | 2 x 2000 W RMS (4 ohms)<br>2 x 1200 W RMS (8 ohms)<br>1 x 4000 W RMS bridged (8 ohms)           |
| Power connection: | Mains input via P-Con (blue), mounting version<br>power supply cord with safety plug (provided) |
| Device fuse:      | 25 A fuse resettable  |
| Frequency range:  | 20 - 20000 Hz   |
| S/N ratio:        | >110 dB   |
| THD:              | <0,1 % at 1 kHz   |

|                    |   |
|--------------------|---|
| Cooling:           | 2 x temperature-controlled fan , air flow from front to rear  |
| Impedance:         | Input: 20 kOhm  |
| Gain:              | 42 dB   |
| Circuitry:         | Class TD  |
| Slew rate:         | 30 V/ $\mu$ s   |
| Damping factor:    | >500  |
| Crosstalk:         | >65 dB  |
| Control elements:  | Power switch, level control per channel, mode switch (stereo/parallel/bridged), groundlift selector   |
| Controls:          | Softstart; short-circuit; Overvoltage; overload; current limiting; DC voltage; overheat   |
| Status LED:        | Power, signal, limit, protect   |
| Connections:       | Input: line via 2 x 3-pin XLR (F) mounting version<br>Output: line via 2 x 3-pin XLR (M) mounting version<br>Output: speaker via 2 x 4-pol SpeakON mounting version (F)<br>Output: 4 x screw plug-in terminal |
| Input sensitivity: | 0,775 V   |
| Color:             | Black, matte, painted   |
| Housing design:    | (19") 48.3 cm rack installation 2 U   |
| Dimensions:        | Width: 48,3 cm<br>Depth: 38,8 cm<br>Height: 8,8 cm  |
| Weight:            | 18,00 kg  |