

# EUROLITE Set 4x LED BAR-12 QCL RGBW + 2x Soft Bag + Controller

4x Spotlight bar with 12 x 4 W 4in1 LED including soft bag and compact DMX controller

Art. No.: 20000407

GTIN:





List price: 831.81 €

incl. 19% VAT.

Features: Logistic

#### **EUROLITE LED BAR-12 QCL RGBW Bar**

LED bar (110cm) with 12 x 4 watt 4in1 QCL RGBW LED

- 12 powerful LEDs 4 W high-power 4in1 QCL RGBW (homogenous color mix)
- Color change adjustable; Dimmer electronic; color blend stepless
- Strobe effect
- The device is cooled by passive convection cooling
- Control via stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
- Flicker-free
- With a beam angle of 17°
- With mounting bracket
- 4 digit 7-segment LED display
- Preprogrammed in LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief
- Silent operation
- Mains input and output for power linking up to 8 units
- For application areas such as: Clubs/dancing school; party room; restaurants, bars and hotels; small rental
- Application possibility: Suspended; wall mounting

## Package contents

1 x light effect, 1 x power cord, 2 x mounting bracket, 2 x knurled screw, 2 x washer, 1 x user

### **EUROLITE SB-12 Soft Bag**

Practical black soft bag for LED bars (1 m length), adjustable divider

- Ideal for 1 or 2 LED bars with 1 meter length
- Made of easy-care nylon
- With divider
- With 2 device compartments
- High-quality workmanship with textile, black
- Interior with foam padding
- 2 carrying straps
- 1 shoulder strap

### **EUROLITE DMX LED EASY Operator 4x4**

Compact DMX controller for 4 LED spotlights with up to 4 colors each

- DMX controller for standard LED spotlights
- Easy handling
- 4 fixtures with RGBW LEDs can be controlled individually or in combination
- DMX channels for red, green, blue, white and master
- Various modes for the DMX channel sequence selectable
- Manual control via 4 faders
- 1 fader for direct RGBW mixing
- Adjustable strobe function
- Blackout function
- 8 integrated show programs
- Preprogrammed 8 scenes/chases
- Can transmit up to 20 DMX channels
- Control via DMX; sound to light via microphone; stand-alone
- Desktop console housing
- For application areas such as: Party room; mobile djs / entertainer
- Silent operation

#### Package contents

- 1 x controller, 1 x external mains adapter, 1 x user manual

## **Technical specifications:**

Weight: 13,47 kg

## **EUROLITE LED BAR-12 QCL RGBW Bar**

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	24 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Lamp type:	LED lamp
LED type:	12 x 4 W high-power 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	2; 4; 5; 6; 9
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling

Preprogrammed in:  LED PC-Control 512; EASY SHOW 1; LED EASY OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain; Light'J; Colorchief  Projection: Flicker-free  Beam angle: 17°  Beam angle (1/12 peak): 17°  Beam angle (1/10 peak): 33°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Length: 110 cm Depth: 6,5 cm Height: 10 cm  Weight: 2,85 kg  Noise classification: Class 0 (no noise at all)  Photobiological safety: Risk Group 0  Power cord  Cable construction: 3 x 0,75 mm² H05RN-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material: Metal  Legal specifications  Special product: Not designed for household room illumination  Intended use: Show effect lighting	Control:	Stand-alone; DMX; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional)
Beam angle: 17°  Beam angle (1/2 peak): 17°  Beam angle (1/10 peak): 33°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Length: 110 cm	Preprogrammed in:	OPERATOR 4x4; LED EASY OPERATOR 4x6; LED EASY OPERATOR DELUXE; Light Captain;
Beam angle (1/2 peak): 17°  Beam angle (1/10 peak): 33°  Housing color: Black  Attachment system: Mounting bracket  Display type: 4 digit 7-segment LED display  Dimensions: Length: 110 cm  Depth: 6,5 cm  Height: 10 cm  Weight: 2,85 kg  Noise classification: Class 0 (no noise at all)  Photobiological safety: Risk Group 0  Power cord  Cable construction: 3 x 0,75 mm² H05RN-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material: Metal  Legal specifications  Special product: Not designed for household room illumination	Projection:	Flicker-free
Beam angle (1/10 peak):  Housing color:  Black  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Length: 110 cm  Depth: 6,5 cm  Height: 10 cm  Weight:  2,85 kg  Noise classification:  Class 0 (no noise at all)  Photobiological safety:  Risk Group 0  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Beam angle:	17°
Housing color:  Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Length: 110 cm Depth: 6,5 cm Height: 10 cm  Weight:  2,85 kg  Noise classification:  Class 0 (no noise at all)  Photobiological safety:  Risk Group 0  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/2 peak):	17°
Attachment system:  Mounting bracket  Display type:  4 digit 7-segment LED display  Dimensions:  Length: 110 cm  Depth: 6,5 cm  Height: 10 cm  Weight:  2,85 kg  Noise classification:  Class 0 (no noise at all)  Photobiological safety:  Risk Group 0  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Beam angle (1/10 peak):	33°
Display type:  4 digit 7-segment LED display  Length: 110 cm Depth: 6,5 cm Height: 10 cm  Weight:  2,85 kg  Noise classification:  Class 0 (no noise at all)  Photobiological safety:  Risk Group 0  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Housing color:	Black
Dimensions:  Length: 110 cm Depth: 6,5 cm Height: 10 cm  Weight:  2,85 kg  Noise classification:  Class 0 (no noise at all)  Photobiological safety:  Risk Group 0  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Attachment system:	Mounting bracket
Depth: 6,5 cm Height: 10 cm  Weight:  2,85 kg  Noise classification:  Class 0 (no noise at all)  Photobiological safety:  Risk Group 0  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Display type:	4 digit 7-segment LED display
Weight:  2,85 kg  Noise classification:  Class 0 (no noise at all)  Photobiological safety:  Risk Group 0  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Dimensions:	Depth: 6,5 cm
Photobiological safety:  Power cord  Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Weight:	
Power cord  Cable construction: 3 x 0,75 mm² H05RN-F  Cable length: Approx. 1,2 m  Mounting bracket  Diameter mounting holes: 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material: Metal  Legal specifications  Special product: Not designed for household room illumination	Noise classification:	Class 0 (no noise at all)
Cable construction:  3 x 0,75 mm² H05RN-F  Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Photobiological safety:	Risk Group 0
Cable length:  Approx. 1,2 m  Mounting bracket  Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Power cord	
Mounting bracket  Diameter mounting holes: 1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material: Metal  Legal specifications  Special product: Not designed for household room illumination	Cable construction:	3 x 0,75 mm² H05RN-F
Diameter mounting holes:  1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm  Material:  Metal  Legal specifications  Special product:  Not designed for household room illumination	Cable length:	Approx. 1,2 m
Material: Metal  Legal specifications  Special product: Not designed for household room illumination	Mounting bracket	
Legal specifications  Special product: Not designed for household room illumination	Diameter mounting holes:	1 x Ø20mm; 1 x Ø11mm; 1 x Ø8mm; 2 x Ø6mm
Special product: Not designed for household room illumination	Material:	Metal
	Legal specifications	
Intended use: Show effect lighting	Special product:	Not designed for household room illumination
	Intended use:	Show effect lighting

# **EUROLITE SB-12 Soft Bag**

Maximum load:	20 kg
Carrying strap:	2 pc/pcs
Transport aid:	1 x shoulder strap
Material:	Textile
Color:	Black
Dimensions:	Width: 107 cm
	Depth: 17 cm
	Height: 18 cm
Weight:	0,60 kg

# **EUROLITE DMX LED EASY Operator 4x4**

Power supply: 100-240 V AC, 50/60 Hz 9V DC 800 mA

Power consumption:	10 W
IP classification:	IP20
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with AC adapter (provided)
Programs:	Preprogrammed 8 scenes/chases
DMX channels:	Output 20
DMX output:	3-pin XLR (F) mounting version
Control:	DMX; sound to light via microphone; stand-alone
Housing color:	Black
Color:	Black
Housing design:	Desktop console housing
Dimensions:	Width: 20 cm
	Depth: 11,5 cm
	Height: 5,5 cm
Weight:	0,86 kg
Noise classification:	Class 0 (no noise at all)