



**List price: 3092.81 €**

incl. 19% VAT.

### Features:

#### EUROLITE LED PMB-8 COB QCL 30W Bar

LED light effect bar with RGBW color mixing, incl. IR remote control

- 8 powerful LEDs 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by low-noise cooling fan
- Control via stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 45°
- With mounting bracket
- LCD display
- Preprogrammed in Light´J; Light Captain
- Very quiet working noise
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; Trade fair and shop fitting; stage; theater; rental
- Application possibility: Standing; suspended; on stand

#### Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

### Logistic

EAN / GTIN: 4026397527957

Weight: 67,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

## ROADINGER Flightcase 4x LED PMB-8 COB QCL

Trunk case, PRO version

- High-quality workmanship with birch multiplex 9 mm, black, laminated
- Interior with foam padding
- Aluminum profile frames 30mm with rounded edges
- 4 hinged, chromium plated case handles
- 7 chrome tip-over locks
- 2 high-quality butterfly locks
- PENN Hardware
- For further information about this product, please refer to the Data Sheet under "Downloads"

## Technical specifications:

---

Weight: 58,80 kg

---

### EUROLITE LED PMB-8 COB QCL 30W Bar

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	240 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Power output:	P-Con (gray), mounting version
Fuse:	T 3 A fuse replaceable
Lamp type:	LED lamp
LED type:	8 x 30 W COB (chip-on-board) 4in1 QCL RGBW (homogenous color mix)
Flash rate:	0 - 20 Hz
DMX channels:	3; 4; 5; 6; 12; 32; 36
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	2 x low-noise cooling fan
Control:	Stand-alone; IR remote control; DMX; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W- DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
Preprogrammed in:	Light J; Light Captain
Projection:	Flicker-free
Beam angle:	45°
Beam angle (1/2 peak):	45°
Beam angle (1/10 peak):	74°
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	LCD display

Material:	Aluminum casting; metal
Dimensions:	Length: 98,0 cm Depth: 16,3 cm Height: 20,6 cm
Weight:	8,65 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Photobiological safety:	Risk Group 0
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 3 x Ø10mm; 4 x Ø8mm; 2 x Ø6mm
Material:	Metal, 2,5 mm
Power cord	
Cable construction:	3 x 1,0 mm <sup>2</sup> H05VV-F
Cable length:	Approx. 1,2 m
Remote control	
Battery:	Button cell 3.0 V CR2025 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

#### **ROADINGER Flightcase 4x LED PMB-8 COB QCL**

Maximum load:	100 kg
Aluminum profile frames:	30 mm
Case handle:	4 pc/pcs
Stop hinge:	7 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Use of brands:	PENN Hardware
Material:	Birch multiplex, 9 mm
Color:	Black, laminated
Device compartment:	99,5 cm x 12 cm x 26 cm
Accessory compartment:	10 cm x 71 cm x 28 cm
Dimensions:	Width: 116 cm Depth: 75 cm Height: 32,5 cm
Weight:	24,20 kg