

EUROLITE Set 4x AKKU MBT-3 Spot MK2 + Flightcase with wheels and changing function

GTIN: 4026397739503







List price: 1843.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU MBT-3 Spot MK2

Light fan for special uplight and beam effects with rechargeable battery

- Strobe effect; fan effect; uplight effect
- Cordless, flexible and versatile
- Silent operation
- 3 powerful LEDs 8 W high-power 4in1 QCL RGBW (homogenous color mix)
 LEDs controlled separately
- 9 integrated show programs
- Direct color selection for 15 preset colors
- Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic;
 Dimmer speed (step response) with adjustable response
- Battery operation up to 16h depending on program used
- Control via stand-alone; master/slave function; sound to light via microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Integrated automatic charging of the battery and status indicator
- Flicker-free
- Space-saving construction
- With a beam angle of 13°
- 4 digit 7-segment LED display
- The device is cooled by passive convection cooling
- Mains input and output for power linking up to 8 units
- Application possibility: Standing; suspended
- Preprogrammed in Light'J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief

Logistic

EAN / GTIN: 4026397739503

Weight: 35,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m Bulky product For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; small rental

Package contents

- 1 x device, 1 x power cord, 1 x user manual, 1 x remote control, 1 x battery

ROADINGER Flightcase 4x AKKU MBT-3 with wheels and charging function

Trunk case with castors

- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks with shut-off function
- 4 castors with 2 locking brakes
- 4 built-in stacking trays in the cover

Technical specifications:

Weight: 35,00 kg

EUROLITE AKKU MBT-3 Spot MK2

| Power supply: | 100-240 V AC, 50/60 Hz |
|--------------------|--|
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided) |
| Cable length: | 1,5 m |
| Power output: | IEC connector (F) mounting version |
| Fuse: | 5 x 20 mm, T 1,6 A fuse replaceable |
| Battery pack type: | 1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh |
| Battery pack: | Battery operation up to 16h depending on program used |
| | Recharging time 4h |
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| Lamp type: | LED lamp |
| LED type: | 3 x 8 W high-power 4in1 QCL RGBW (homogenous color mix) |
| Inclination angle: | 180 ° |
| Flash rate: | 0 - 25 Hz |
| DMX channels: | 3; 4; 8; 12; 16 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | Passive convection cooling |
| • | |

| Control: | Stand-alone; master/slave function; sound to light via microphone; IR remote control; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
|------------------------|--|
| Preprogrammed in: | Light'J; Light Captain; EASY SHOW 1; EASY SHOW 3; EASY SHOW 2; Colorchief |
| Projection: | Flicker-free |
| Setup: | Space-saving construction |
| Beam angle: | 13° |
| Beam angle (1/2 peak): | 13° |
| Housing color: | Black |
| Display type: | 4 digit 7-segment LED display |
| Dimensions: | Length: 30,5 cm |
| | Width: 9,5 cm |
| | Height: 22 cm |
| Weight: | 4,15 kg |
| Noise classification: | Class 0 (no noise at all) |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |

ROADINGER Flightcase 4x AKKU MBT-3 with wheels and charging function

| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
|--------------------------|--|
| Fuse: | 5 x 20 mm, T 5 A fuse replaceable |
| Aluminum profile frames: | 30 mm |
| Case handle: | 2 pc/pcs |
| Stop hinge: | 2 pc/pcs |
| Lock: | Butterfly lock: 2 pc/pcs with shut-off function |
| Transport aid: | 4 x castors with 2 locking brakes4 x built-in stacking trays in the cover |
| Material: | Plywood multi-layer glued |
| Color: | Black, laminated |
| Inside dimensions: | 58 cm x 44,5 cm x 23 cm |
| Accessory compartment: | 58 cm x 13,5 cm x 23 cm |
| Dimensions: | Width: 66 cm |
| | Depth: 52 cm |
| | Height: 41 cm |
| Weight: | 17,30 kg |