



List price: 2569.21 €

incl. 19% VAT.

Features:

EUROLITE LED PLL-576 CW/WW Panel

DMX-controlled surface light with 576 dual white LEDs, QuickDMX port, diffuser and barn doors

- 288 powerful LEDs 0,5 W SMD 5730 warm white (WW)
- 288 powerful LEDs 0,5 W SMD 5730 cold white (CW)
- Variable color temperature 3000 K - 6000 K
- Additional frost filter provides a wide, soft and homogeneous light
- 4 barn doors to avoid blinding the audience and for protection during transport
- Direct color temperature selection for 69 preset values
- Dimmer electronic
- Flicker-free
- With a beam angle of 120°
- The device is cooled by temperature-controlled fan
- Very high color rendering index (CRI)
- LCD display
- Rubber feet
- Control via DMX; master/slave function; stand-alone; quick select potentiometer for brightness and color temperature; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
- With mounting bracket
- For application areas such as: Video and photography; stage; Trade fair and shop fitting; rental
- Mains input and output for power linking up to 8 units
- Preprogrammed in Light Captain
- Very quiet working noise
- Application possibility: Suspended; standing; on stand

Package contents

- 1 x spotlight, 1 x user manual, 1 x power cord, 1 x frost filter, 4 x knurled screw

Logistic

EAN / GTIN: 4026397739589

Weight: 47,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

Bulky product

ROADINGER Flightcase 4x PLL-576 CW/WW with wheels

Trunk case with castors, PRO version

- With 4 device compartments
- With 1 accessory compartment
- High-quality workmanship with birch multiplex 6,5 mm, black
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 25mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 castors with 2 locking brakes
- Branded hardware

Technical specifications:

Weight: 45,20 kg

EUROLITE LED PLL-576 CW/WW Panel

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	160 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug
Power output:	1 x P-Con (gray), mounting version
Fuse:	T 3,15 A fuse fix in power supply
Lamp type:	LED lamp
LED type:	288 x 0,5 W SMD 5730 cold white (CW) 288 x 0,5 W SMD 5730 warm white (WW)
DMX channels:	2-1; 2-2; 3-1; 3-2; 4
DMX input:	3-pin XLR (M) mounting version 5-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	DMX; master/slave function; stand-alone; quick select potentiometer for brightness and color temperature; CRMX by LumenRadio via USB (optional); QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional)
Preprogrammed in:	Light Captain
Projection:	Flicker-free
Beam angle:	120°
Beam angle (1/2 peak):	120°
Color temperature:	3000K - 6000K adjustable
Color rendering index (CRI):	93 Ra

Illuminance in Lux (lx): <hr/> Housing color: Attachment system: Display type: Transport aid: Dimensions: Weight: Noise classification: <hr/> Legal specifications Special product: Intended use:	Cold white (CW) 1m: 3752 lx, 3m: 453 lx, 6m: 134 lx Warm white (WW) 1m: 3664 lx, 3m: 445 lx, 6m: 132 lx All 1m: 5667 lx, 3m: 690 lx, 6m: 204 lx Black Mounting bracket LCD display Rubber feet Length: 44 cm Width: 19,8 cm Height: 22,3 cm 6,00 kg Class 1 (very slight noise, suitable for noise-sensitive environments) <hr/> Not designed for household room illumination Show effect lighting
---	---

ROADINGER Flightcase 4x PLL-576 CW/WW with wheels

Maximum load:	50 kg
Aluminum profile frames:	25 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x castors with 2 locking brakes
Use of brands:	Branded hardware
Material:	Birch multiplex, 6,5 mm, laminated
Color:	Black
Device compartment:	22,5 cm x 47 cm x 25 cm
Inside dimensions:	100 cm x 47 cm x 25 cm
Accessory compartment:	7 cm x 47 cm x 25 cm
Dimensions:	Width: 1,045 cm Depth: 51,5 cm Height: 29,5 cm
Weight:	18,90 kg