



List price: 1069.81 €

incl. 19% VAT.

Features:

EUROLITE LED CLS-18 QCL RGB/WW 18x7W

LED floodlight with RGB/WW color mixing, barn doors, IR remote control and frost filter

- Additional frost filter provides a wide, soft and homogeneous light
 - 3 buttons on the remote control for saving your own settings
 - 18 powerful LEDs 7 W 4in1 QCL RGB/WW (homogenous color mix)
 - Color blend stepless; color change adjustable; color fade adjustable; Dimmer electronic; Dimmer speed (step response) adjustable; white balance
 - Strobe effect
 - The device is cooled by temperature-controlled fan
 - Control via stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
 - Flicker-free
 - With a beam angle of 11°
 - With mounting bracket
 - OLED display
 - Very quiet working noise
 - Preprogrammed in Light´J; EASY SHOW 2; EASY SHOW 3
 - Direct color temperature selection for 3100 preset values
 - Rubber feet
 - For application areas such as: Wedding/gala/events; stage; theater; mobile djs / entertainer; restaurants, bars and hotels
 - Application possibility: Standing; suspended; on stand
- knurled screw**
- M4 thread

Package contents

Logistic

EAN / GTIN: 4026397733020

Weight: 22,00 kg

Length: 0.00 m

Width: 0.00 m

Height: 0.00 m

- 1 x device, 1 x power cord, 1 x frost filter, 1 x remote control, 4 x knurled screw, 1 x user manual

ROADINGER Flightcase 2x LED CLS-18 QCL RGB/WW

Trunk case

- High-quality workmanship with plywood multi-layer glued 9 mm, black, laminated
- Interior with foam padding
cover with foam padding
- Aluminum profile frames 30mm with rounded edges
- 2 hinged, chromium plated case handles
- 2 chrome tip-over locks
- 2 high-quality butterfly locks
- 4 rubber feet
- For further information about this product, please refer to the Data Sheet under "Downloads"

Technical specifications:

Weight: 21,23 kg

EUROLITE LED CLS-18 QCL RGB/WW 18x7W

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	104 W
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug included
Power output:	1 x PowerCON (gray)
Fuse:	T 6,3 A fuse fix on board
Lamp type:	LED lamp
LED type:	18 x 7 W 4in1 QCL RGB/WW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	1 x 3-pin XLR (M) mounting version 1 x 5-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version 1 x 5-pin XLR (F) mounting version
Cooling:	Temperature-controlled fan
Control:	Stand-alone; DMX; QuickDMX (optional); W-DMX by wireless solution (optional); CRMX by LumenRadio (optional); master/slave function; sound to light via microphone; IR remote control
Preprogrammed in:	Light`J; EASY SHOW 2; EASY SHOW 3
Projection:	Flicker-free
Beam angle:	11°
Beam angle (1/2 peak):	11° Frost filter 15°
Beam angle (1/10 peak):	26° Frost filter 37°

Housing color:	Black matte
Attachment system:	Mounting bracket
Display type:	OLED display
Transport aid:	Rubber feet
Dimensions:	Length: 39,6 cm Width: 14,3 cm Height: 21,3 cm
Weight:	4,75 kg
Noise classification:	Class 1 (very slight noise, suitable for noise-sensitive environments)
Mounting bracket	
Diameter mounting holes:	3 x Ø11mm; 2 x Ø8mm; 8 x Ø15mm
Material:	Metal, 2 mm
Power cord	
Cable construction:	3 x 1,0 mm ² H05VV-F
Cable length:	Approx. 1,2 m
Frost filter	
Diameter mounting holes:	4 x Ø4,5mm
Material:	Plastic, 2 mm
Dimensions:	Width: 28,3 cm Height: 11,6 cm
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Barndoor	
Material:	Metal, 0,8 mm
Dimensions:	Width: 46,5 cm Height: 28,5 cm
Knurled screw	
Thread:	M4 thread x 8 mm
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting

ROADINGER Flightcase 2x LED CLS-18 QCL RGB/WW

Aluminum profile frames:	30 mm
Case handle:	2 pc/pcs
Stop hinge:	2 pc/pcs
Lock:	Butterfly lock: 2 pc/pcs
Transport aid:	4 x rubber feet
Material:	Plywood multi-layer glued, 9 mm
Color:	Black, laminated
Device compartment:	12 cm x 40 cm x 28 cm
Accessory compartment:	10,5 cm x 47 cm x 28 cm
Dimensions:	Width: 51,5 cm

Depth: 52,5 cm
Height: 35,5 cm

Weight: 10,85 kg
