

EUROLITE Set 4x AKKU UP-4 QCL Spot QuickDMX MK2 + Plastic case

Art. No.: 20001038

GTIN: 4026397710106







List price: 1605.31 €

incl. 19% VAT.

Features:

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Bright battery powered LED uplight with 10 W 4in1 LEDs and QuickDMX

- Integrated QuickDMX transceiver for wireless DMX control
- Cordless, flexible and versatile
- 4 powerful LEDs 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Dimmer electronic; Dimmer speed (step response) adjustable; color fade adjustable speed; color change adjustable speed; white balance adjustable; color blend adjustable; frost filter; color selection manual; program selection manual; pulse-width modulation; Energy-saving mode; Emergency lighting function in case of power failure
- Multi beam effect; spot effect; wash effect; strobe effect
- 36 integrated show programs
- Direct color selection for 15 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM
- Up to 6 transmitters can be operated in parallel without interference
- DMX fail mode (blackout; hold; static; full on)
- With a beam angle of 7°
- With bracket for floor use
- Mains input and output for power linking up to 8 units
- For application areas such as: Wedding/gala/events; mobile use; mobile djs / entertainer; rental
- Silent operation
- Application possibility: Standing; suspended
- Battery operation up to 9h depending on program used
- Integrated automatic charging of the battery and status indicator
- With a KENSINGTON LOCK theft protection

Logistic

EAN / GTIN: 4026397710106

Weight: 19,00 kg Length: 0.00 m Width: 0.00 m Heigth: 0.00 m

- Flicker-free
- QuickDMX: operating range up to 600m in the open air
- Monochrome OLED display
- Display of the remaining battery life for the current setting
- Charge status indicator
- 3 buttons on the remote control for saving your own settings

Package contents

- 1 x spotlight, 1 x user manual, 1 x declaration of conformity, 1 x power cord, 1 x remote control,

1 x battery, 1 x frost filter, 1 x knurled screw

ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

Carrying case

- With 4 device compartment
- High-quality workmanship with plastic, black
- Interior with foam padding
cover with foam padding
- Rugged carrying handle
- 4 high-quality spring locks with shut-off function
- 4 plastic feet
- For application areas such as: Mobile use; rental; mobile djs / entertainer

Package contents

1 x case

Technical specifications:

Weight: 15,62 kg

EUROLITE AKKU UP-4 QCL Spot QuickDMX MK2

Power supply:	100-240 V AC, 50/60 Hz
IP classification:	IP20
Protection class:	Protection class I
Power connection:	Mains input via P-Con (blue), mounting version power supply cord with safety plug (provided)
Cable construction:	3 x 1,0 mm ² H05VV-F
Power output:	P-Con (gray), mounting version
Battery pack type:	1 x lithium ion 14,8 V, 6600 mAh, 97,68 Wh
Battery pack:	Battery operation up to 9h depending on program used
	Recharging time 3h
Lamp type:	LED lamp
LED type:	4 x 10 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	27 Hz
DMX channels:	3; 4; 6; 8; 11
DMX input:	3-pin XLR (M) mounting version
DMX output:	3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	IR remote control; QuickDMX; DMX; stand-alone; sound to light via microphone; wireless Master/slave function; RDM

PWM frequency: Range: QuickDMX: range up to 600m in the open air Carrier frequency: 2,4 GHz Parallel mode: Max. 6 transmitter Modulation: GFSK DMX fail mode: Blackout; hold; static; full on Beam angle: 7° Beam angle (1/2 peak): 7° Frost filter 20° Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: 500 mm Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: altery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications Special product: Not designed for household room illumination	Projection:	Flicker-free
Carrier frequency: Parallel mode: Max. 6 transmitter Modulation: GFSK DMX fail mode: Beam angle: 7° Beam angle (1/2 peak): 7° Frost filter 20° Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	PWM frequency:	3000 Hz
Parallel mode: Modulation: GFSK DMX fail mode: Beam angle: 7° Beam angle: 7° Beam angle (1/2 peak): Frost filter 20° Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: 500 mm Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Range:	QuickDMX: range up to 600m in the open air
Modulation: DMX fail mode: Beam angle: 7° Beam angle (1/2 peak): Frost filter 20° Beam angle (1/10 peak): Frost filter 42° Distance to wall: Attachment system: Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Carrier frequency:	2,4 GHz
DMX fail mode: Beam angle: 7° Beam angle (1/2 peak): 7° Frost filter 20° Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Parallel mode:	Max. 6 transmitter
Beam angle: 7° Beam angle (1/2 peak): 7° Frost filter 20° Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: 500 mm Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Modulation:	GFSK
Beam angle (1/2 peak): 7° Frost filter 20° Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: 500 mm Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	DMX fail mode:	Blackout; hold; static; full on
Frost filter 20° Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: 500 mm Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Beam angle:	
Beam angle (1/10 peak): 18° Frost filter 42° Distance to wall: 500 mm Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Beam angle (1/2 peak):	
Distance to wall: Distance to wall: Attachment system: Bracket for floor use Display type: Monochrome OLED display Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in		Frost filter 20°
Distance to wall: Attachment system: Bracket for floor use Display type: Monochrome OLED display Battery runtime calculation, charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Beam angle (1/10 peak):	18°
Attachment system: Display type: Monochrome OLED display Battery runtime calculation, charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications		Frost filter 42°
Display type: Display: Battery runtime calculation, charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Distance to wall:	500 mm
Display: Battery runtime calculation , charge status indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Attachment system:	Bracket for floor use
indicator Material: Metal, painted Theft protection: KENSINGTON LOCK Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications	Display type:	Monochrome OLED display
Theft protection: KENSINGTON LOCK Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in	Display:	· · · · · · · · · · · · · · · · · · ·
Dimensions: Length: 15,4 cm Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications	Material:	Metal, painted
Width: 13,3 cm Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications	Theft protection:	KENSINGTON LOCK
Height: 15,8 cm Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications	Dimensions:	Length: 15,4 cm
Weight: 2,83 kg Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications		Width: 13,3 cm
Noise classification: Class 0 (no noise at all) Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications		Height: 15,8 cm
Remote control Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications	Weight:	2,83 kg
Battery: 1 x button cell 3.0 V CR2032 lithium manganese built-in Legal specifications	Noise classification:	Class 0 (no noise at all)
built-in Legal specifications	Remote control	
	Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Special product: Not designed for household room illumination	Legal specifications	
	Special product:	Not designed for household room illumination
Intended use: Show effect lighting	Intended use:	Show effect lighting

ROADINGER Plastic Case for 4x AKKU UP-4 QCL Spot QuickDMX MK2

Maximum load:	25 kg
Carrying handle:	1 pc/pcs
Lock:	Spring lock: 4 pc/pcs with shut-off function
Transport aid:	4 x plastic feet
Material:	Plastic
Color:	Black
Inside dimensions:	49 cm x 36 cm x 13 cm
Device compartment:	16 cm x 13,5 cm x 16 cm
Accessory compartment:	8 cm x 30,5 cm x 16 cm
Dimensions:	Length: 55 cm
	Depth: 42,5 cm
	Height: 21 cm
Weight:	4,30 kg