

EUROLITE AKKU IP Flat Light SMD bk

Flat IP65 spotlight in black with 81 x 0,2 W 4in1 QCL RGBW LED, QuickDMX transceiver

Art. No.: 4170051

GTIN: 4026397704334



List price: 296.31 €

incl. 19% VAT.

Features:

- Integrated QuickDMX transceiver for wireless DMX control
- Compact and bright
- Battery operation up to 16h depending on program used
- 81 powerful LEDs 0,2 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
- Dimmer speed (step response) adjustable; color selection manual; color change adjustable; color fade adjustable
- Strobe effect
- Direct color selection for 30 preset colors
- The device is cooled by passive convection cooling
- Control via master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
- Flicker-free
- LCD display
- Suitable for outdoor use IP65
- For application areas such as: Small rental; rental; wedding/gala/events; mobile djs / entertainer
- Preprogrammed in Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J
- Cordless, flexible and versatile
- Integrated automatic charging of the battery and status indicator
- Silent operation
- Application possibility: Standing

Package contents

- 1 x device, 1 x external mains adapter, 2 x battery, 1 x remote control, 1 x user manual

Logistic

EAN / GTIN: 4026397704334

Weight: 1,85 kg

Length: 0.27 m

Width: 0.20 m

Height: 0.11 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz 12,6 V DC 2500 V
IP classification:	IP65
Protection class:	Protection class III
Power connection:	Mains input via coaxial power connector (M) mounting version power supply cord with Euro plug (provided) Battery/battery pack
Battery pack type:	2 x lithium ion 11,1 V, 2600 mAh, 28,86 Wh
Battery pack:	Battery operation up to 16h depending on program used Recharging time 4h
Lamp type:	LED lamp
LED type:	81 x 0,2 W SMD 5050 4in1 QCL RGBW (homogenous color mix)
Flash rate:	1 - 23 Hz
DMX channels:	3; 4; 6; 8; 10
Cooling:	Passive convection cooling
Control:	Master/slave function; IR remote control; QuickDMX; stand-alone; sound to light via microphone
Preprogrammed in:	Light Captain; EASY SHOW 1; EASY SHOW 2; EASY SHOW 3; Light J
Projection:	Flicker-free
Carrier frequency:	2,4 GHz
Beam angle (1/10 peak):	120°
Housing color:	Black
Display type:	LCD display
Dimensions:	Length: 17,2 cm Width: 13,8 cm Depth: 6,4 cm
Weight:	1,60 kg
Noise classification:	Class 0 (no noise at all)
Remote control	
Battery:	1 x button cell 3.0 V CR2032 lithium manganese built-in
Legal specifications	
Special product:	Not designed for household room illumination
Intended use:	Show effect lighting