

EUROLITE LED B-40 Laser Beam Effect

LED beam effect with RGBW color mixing and RG laser

Art. No.: 51741087

GTIN: 4026397647396



List price: 403.41 €

incl. 19% VAT.

Features:

- 2 laser diodes project hundreds of red and green laser beams
 - 5 powerful LEDs 8 W high-power 4in1 QCL RGBW
3 segments controlled separately
 - Laser; multi beam effect; strobe effect
 - Laser class 2M
 does not require additional protective measures or appointment of a laser safety officer
 - 7 integrated show programs
 - Rotation speed stepless; color blend stepless; Dimmer electronic
 - Control via stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
 - The device is cooled by passive convection cooling
 - With mounting bracket
 - Monochrome 4 digit 7-segment LED display
 - Mains input and output for power linking up to 8 units
 - Preprogrammed in Light'J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
 - For application areas such as: Clubs/dancing school; party room; mobile djs / entertainer; rental
 - Application possibility: Standing; suspended; on stand
- Package contents**
- 1 x light effect, 1 x power cord, 1 x omega bracket, 1 x user manual, 1 x remote control, 4 x screw, 4 x washer

Logistic

EAN / GTIN: 4026397647396
Weight: 6,25 kg
Length: 0.41 m
Width: 0.40 m
Height: 0.52 m

Technical specifications:

Power supply:	100-240 V AC, 50/60 Hz
Power consumption:	65 W
IP classification:	IP20
Power connection:	Mains input via IEC connector (M) mounting version power supply cord with safety plug (provided)
Power output:	1 x IEC connector (F) mounting version
Fuse:	5 x 20 mm, T 1 A fuse replaceable
Lamp type:	LED lamp
LED type:	5 x 8 W high-power 4in1 QCL RGBW
Flash rate:	0 - 20 Hz
Laser class:	2M
Laser color:	R/G
Laser module:	Green (G) 40 mW 532nm Red (R) 100 mW 650nm
DMX channels:	3; 10; 22
DMX input:	1 x 3-pin XLR (M) mounting version
DMX output:	1 x 3-pin XLR (F) mounting version
Cooling:	Passive convection cooling
Control:	Stand-alone; DMX; sound to light via microphone; master/slave function; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); IR remote control
Preprogrammed in:	Light J; LED PC-Control 512; EASY SHOW 1; Light Captain; EASY SHOW 2; EASY SHOW 3; Colorchief
Housing color:	Black
Attachment system:	Mounting bracket
Display type:	Monochrome 4 digit 7-segment LED display
Dimensions:	Width: 31 cm Depth: 31 cm Height: 39 cm
Weight:	4,20 kg
Noise classification:	Class 2 (slight noise)