eurolite®

EUROLITE LED IP FL-100 SMD RGB

Outdoor floodlight (IP65) with RGB LEDs and IR remote control

Art. No.: 51914609 GTIN: 4026397715897











List price: 117.81 €

incl. 19% VAT.

Features:

- Extremely slim housing in an appealing design
- 108 powerful LEDs SMD 2835 R/G/B
- Direct color selection for 16 preset colors
- The device is cooled by passive convection cooling
- Control via IR remote control
- With a beam angle of 70°
- With mounting bracket
- Color change automatic; program selection manual; color selection manual; color fade adjustable; program speed adjustable; Dimmer electronic
- Strobe effect
- Suitable for outdoor use IP65
- For application areas such as: Clubs/dancing school; stage; installation; mobile djs / entertainer; restaurants, bars and hotels
- Application possibility: Suspended
- Silent operation
- Package contents
- 1 x device, 1 x remote control, 1 x battery, 2 x user manual

Technical specifications: Power supply: 100-240 V AC, 50/60 Hz Power consumption: 100 W IP classification: IP65

Logistic

EAN / GTIN: 4026397715897 Weight: 2,05 kg Length: 0.32 m Width: 0.28 m Heigth: 0.04 m

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Protection class:	Protection class I
Power connection:	Fixed power supply cord with safety plug
Cable construction:	3 x 1,0 mm ² H05RN-F
Cable length:	Approx. 1 m
Lamp type:	LED lamp
LED type:	108 x SMD 2835 R/G/B
Cooling:	Passive convection cooling
Control:	IR remote control
Beam angle:	70°
Beam angle (1/2 peak):	70°
Beam angle (1/10 peak):	120°
Color of light:	Switching colors
Luminous flux:	4479 lm
Housing color:	Black
Attachment system:	Mounting bracket
Material:	Aluminum casting
Dimensions:	Width: 30,00 cm
	Depth: 4,2 cm
	Height: 24,5 cm
Weight:	1,92 kg
Noise classification:	Class 0 (no noise at all)
Energy efficiency class (A - G):	G
EPREL-Nr:	1509778
Mounting bracket	
Diameter mounting holes:	3 x Ø8mm
Material:	Metal, 2 mm
Remote control	