

EUROLITE LED CBB-2 WW/CW Fairlight

LED light effect bar with WW/CW COB LEDs, incl. IR remote control

Art. No.: 51930272

GTIN: 4026397686746



List price: 320.11 €

incl. 19% VAT.

Features:

- 2 powerful LEDs 50 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix)
- Variable color temperature 2400 K - 5000 K
- Dimmer electronic
- Strobe effect
- Integrated show programs
- Direct color selection for 27 preset colors
- The device is cooled by cooling fan
- Control via stand-alone; DMX; IR remote control; quick select potentiometer for brightness and color temperature; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional)
- Flicker-free
- With a beam angle of 40°
- Very high color rendering index (CRI)
- With mounting bracket
- 4 digit 7-segment LED display
- For application areas such as: Trade fair construction; theater; video and photography
- Preprogrammed in Light Captain; Colorchief
- Mains input and output for power linking up to 8 units

Package contents

- 1 x spotlight, 1 x power cord, 1 x remote control, 1 x battery, 1 x user manual

Logistic

EAN / GTIN: 4026397686746

Weight: 4,00 kg

Length: 0.30 m

Width: 0.32 m

Height: 0.21 m

Technical specifications:

| | |
|------------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 80 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Lamp type: | LED lamp |
| LED type: | 2 x 50 W COB (chip-on-board) 2in1 BCL CW/WW (homogenous color mix) |
| Flash rate: | 0 - 20 Hz |
| DMX channels: | 2; 3; 4; 6 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Cooling: | 1 x cooling fan |
| Control: | Stand-alone; DMX; IR remote control; quick select potentiometer for brightness and color temperature; master/slave function; sound to light via microphone; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional) |
| Preprogrammed in: | Light Captain; Colorchief |
| Projection: | Flicker-free |
| Beam angle: | 40° |
| Beam angle (1/2 peak): | 40° |
| Beam angle (1/10 peak): | 75° |
| Color temperature: | 2400K - 5000K adjustable |
| Color rendering index (CRI): | 94 Ra |
| Illuminance in Lux (lx): | Warm white (WW) 1m: 928 lx, 3m: 123 lx, 6m: 36 lx Cold white (CW) 1m: 1662 lx, 3m: 220 lx, 6m: 65 lx All 1m: 2522 lx, 3m: 331 lx, 6m: 97 lx |
| Housing color: | Black |
| Attachment system: | Mounting bracket |
| Display type: | 4 digit 7-segment LED display |
| Material: | Metal; aluminum casting; plastic |
| Dimensions: | Width: 26,6 cm Depth: 16,95 cm Height: 19,4 cm |
| Weight: | 3,57 kg |
| Noise classification: | Class 2 (slight noise) |
| Photobiological safety: | Risk Group 0 |
| Power cord | |
| Cable construction: | 3 x 1,0 mm ² H05RN-F |
| Cable length: | Approx. 1,2 m |
| Remote control | |

| | |
|--------------------------|---|
| Battery: | 1 x button cell 3.0 V CR2025 lithium manganese built-in |
| <hr/> | |
| Barndoor | |
| <hr/> | |
| Material: | Metal, 0,8 mm |
| <hr/> | |
| Mounting bracket | |
| <hr/> | |
| Diameter mounting holes: | 1 x Ø11mm; 2 x Ø8mm |
| <hr/> | |
| Material: | Metal, 2,5 mm |
| <hr/> | |
| Legal specifications | |
| <hr/> | |
| Special product: | Not designed for household room illumination |
| <hr/> | |
| Intended use: | Show effect lighting |
| <hr/> | |