

EUROLITE LED PIX-12 Swing QCL Zoom Bar

Art. No.: 51930386

Motorized tiltable LED light effect bar with 12 high-performance LEDs, two zoom ranges from 2° to 28° and 164 effect LEDs



List price: 1486.31 €

incl. 19% VAT.

Features:

- 12 powerful LEDs 40 W 4in1 QCL RGBW (homogenous color mix) - LEDs controlled separately
- With a beam angle of 2° - 28°
- 164 powerful LEDs 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix)
- With a beam angle of 120°
- Beam effect; strobe effect; uplight effect
- Positioning within 180° TILT
- Exact 16 bit resolution at Dimmer
- Zoom motor driven
- Color blend stepless; background color adjustable; program speed adjustable; running light adjustable; dimmer curves with adjustable response; Dimmer speed (step response) adjustable; pulse-width modulation variable
- 6 integrated show programs
- Control via stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Art-Net; RDM
- DMX fail mode (hold; blackout; auto)
- The device is cooled by cooling fan at the base
- Flicker-free
- With omega bracket
- Monochrome LCD display
- 4 rubber feet
- Mains input and output for power linking up to 8 units
- Preprogrammed in Light Captain
- For application areas such as: Clubs/dancing school; stage; concerts/FoH's; rental
- Application possibility: Standing; suspended

Package contents

Logistic

EAN / GTIN: 4026397737127

Weight: 17,50 kg

Length: 1.07 m

Width: 0.37 m

Height: 0.19 m

- 1 x light effect, 1 x user manual, 1 x power cord, 2 x omega bracket

Technical specifications:

| | |
|--------------------------|---|
| Power supply: | 100-240 V AC, 50/60 Hz |
| Power consumption: | 310 W |
| IP classification: | IP20 |
| Protection class: | Protection class I |
| Power connection: | Mains input via P-Con (blue), mounting version power supply cord with safety plug |
| Cable construction: | 3 x 1,5 mm ² H05VV-F |
| Cable length: | 1,4 m |
| Power output: | P-Con (gray), mounting version |
| Device fuse: | 5 x 20 mm, T 3 A fuse replaceable |
| Lamp type: | LED lamp |
| LED type: | 12 x 40 W 4in1 QCL RGBW (homogenous color mix) 164 x 0,2 W SMD 5050 3in1 TCL RGB (homogenous color mix) |
| Max. TILT movement: | 180° exact positioning (16 bit resolution) auto position correction (feedback) |
| Flash rate: | 1 - 20 Hz |
| Equipment: | Zoom motor driven |
| DMX channels: | 28; 34; 67 |
| DMX input: | 3-pin XLR (M) mounting version |
| DMX output: | 3-pin XLR (F) mounting version |
| Network connection: | Protocol: Art-Net 3 via 2x RJ-45 E-Con (F) mounting version |
| Cooling: | 1 x cooling fan at the base |
| Control: | Stand-alone; master/slave function; DMX; QuickDMX via USB (optional); W-DMX by wireless solution via USB (optional); CRMX by LumenRadio via USB (optional); Art-Net; RDM |
| Preprogrammed in: | Light Captain |
| Projection: | Flicker-free |
| DMX fail mode: | Hold; blackout; auto |
| Beam angle: | 120° 2° - 28° |
| Beam angle (1/2 peak): | Ambient light 120° multicolor |
| Beam angle (1/2 peak): | Beam 2 - 20° |
| Beam angle (1/10 peak): | Beam 2 - 28° |
| Illuminance in Lux (lx): | Narrow red (R) 1m: 8706 lx, 3m: 1789 lx, 6m: 903 lx Narrow green (G) 1m: 12942 lx, 3m: 2762 lx, 6m: 1509 lx Narrow blue (B) 1m: 1924 lx, 3m: 470 lx, 6m: 257 lx Narrow cold white (CW) 1m: 13809 lx, 3m: 2917 lx, 6m: 1573 lx Narrow all 1m: 35732 lx, 3m: 7693 lx, 6m: 4097 lx |

Wide red (R) 1m: 1884 lx, 3m: 513 lx, 6m: 148 lx
Wide green (G) 1m: 3154 lx, 3m: 880 lx, 6m: 256 lx
Wide blue (B) 1m: 538 lx, 3m: 152 lx, 6m: 44 lx
Wide cold white (CW) 1m: 3275 lx, 3m: 885 lx, 6m: 257 lx
Wide all 1m: 8576 lx, 3m: 2363 lx, 6m: 682 lx

| | |
|----------------------|--|
| Housing color: | Black |
| Attachment system: | 2x omega bracket |
| Display type: | Monochrome LCD display |
| USB port: | Type A |
| Transport aid: | 4 x rubber feet |
| Material: | Metal, painted |
| Dimensions: | Width: 100 cm Depth: 12 cm Height: 28,5 cm |
| Weight: | 15,70 kg |
| Legal specifications | |
| Special product: | Not designed for household room illumination |
| Intended use: | Show effect lighting |
