

EUROLITE Corda di sicurezza AG-15 4x1000mm fino a 15kg

Corda di sicurezza di alta qualità

Art.n.: 58010364

GTIN: 4026397491302



Prezzo di listino: 11.31 €

incl. 19% IVA

Descrizione :

EUROLITE Safety bonds

The EUROLITE safety bonds comply with the current regulation of the German professional insurance association as summed up in BGI 810-3:2007-03 Loads above persons. The safety bonds are constructed in accordance with the European standards DIN EN 12385-4:2008-06 and DIN 56927:2009-03.

The safety bonds are manufactured by a renowned German supplier and are tested by the LGA, an independent and accredited testing institute. The breaking load testified by the LGA is documented in the test report according to DIN EN 10204 required by the German professional insurance association.

Clearly, every user can secure loads above persons with these safety bonds in all areas where the BGV C1 is required.

Logistica

EAN / GTIN: 4026397491302

Peso : 0,10 kg

Lunghezza : 0.17 m

Larghezza : 0.18 m

Altezza : 0.03 m

Features :

- Per la messa in sicurezza di carichi sopra le persone
- Corda a trefoli rotondi 6 x 19 con inserto in fibra
- Con due redance
- Complies with DIN EN 12385-4:2008-06 and DIN 56927:2009-03
- Fune con redancia e connettore
- Per maggiori informazioni su questo prodotto, consultare "Download" nella scheda tecnica

Dotazione della fornitura

- 1 x Cavo d'arresto, 1 x Connettore

Dati tecnici :

Carico da assicurare (BGV C1):	Max. 15 kg
Struttura funicolare:	6 x 19 FC
Classe di resistenza della fune:	1770
Norma:	DIN EN 12385-4:2008-06, DIN 56927:2009-03
Resistenza nominale della fune:	1770 N/mm ²
Superficie dei fili:	Zincato
Colore:	Argento
Intervallo di temperatura:	-40° C - +100° C
Misure:	Lunghezza: 100 cm Diametro: Ø 0,40 cm
Peso:	0,10 kg
Peso in lunghezza:	0,0554 kg/m
